

Liquid Tight Flexible Conduit Fittings

PRODUCT FEATURES

- Material: Nickel Plated Brass
- Ingress Protection: IP65
- Temperature range: -25°C to +105°C
- Smooth inside for easier wire pulling
- Will not damage conductors
- Straight, external Male thread
- Multipart compression fitting (Body, Compression Nut, Sealing Ring, Ferrule Grounding Cone, Sealing Washer, Locknut & Insulating Throat)
- Supplied with insulating throat
- High tensile strength
- Chemical and oil resistant
- Corrosion-resistant
- Conforms to EN 61386

Type BLT



PRODUCT LIST

Part Number	Metric Size	Thread Diameter	Minimum Bore	Across Flats	Thread Length	Length	Packing
LP410BLT2020	20	20.0	14.8	28.6	12.0	38.1	1000
LP410BLT2525	25	25.0	18.8	34.9	13.5	42.9	1000
LP410BLT3232	32	32.0	25.8	42.4	17.5	46.0	1000
LP410BLT4040	40	40.0	32.3	53.0	18.0	55.6	1000
LP410BLT5050	50	50.0	39.2	59.0	23.0	66.7	1000

RELATED PRODUCT

CONDUIT	Type PVC-ODL	Type PVC-OD	Type PVC-LSZH	Type PVC-LT
				

all dimensions are nominal value in mm
refer to our catalogue for the complete product range