

Liquid Tight Flexible Conduit Fittings

PRODUCT FEATURES

- Material: Nickel Plated Brass
- Ingress Protection: IP66, IP67, IP68 (5bar) & IP69
- Temperature range: -25°C to +105°C
- Smooth inside for easier wire pulling
- Will not damage conductors
- Straight, external Male thread
- Multipart compression fitting (Body, Compression Nut, Nylon Compression Seal, Earthing Ferrule & Insulating Throat)
- Supplied with insulating throat
- High tensile strength
- Chemical and oil resistant
- Corrosion-resistant
- Conforms to EN 61386

Type DLT



PRODUCT LIST

Part Number	Conduit Metric Size	Thread A	B	C	D	E	F (A/F)
LP414ODLT20	20	M20x1.5	12.0	21.5	29.0	14.5	26.0
LP414ODLT25	25	M25x1.5	14.0	26.5	35.0	18.0	33.0
LP414ODLT32	32	M32x1.5	15.0	30.8	42.0	24.6	40.0
LP414ODLT40	40	M40x1.5	16.0	31.5	52.0	32.7	50.0
LP414ODLT50	50	M50x1.5	18.0	35.0	58.0	37.7	58.0

RELATED PRODUCT

CONDUIT	Type PVC-ODL	Type PVC-OD	Type PVC-LSZH	Type PVC-LT
				

all dimensions are nominal value in mm
refer to our catalogue for the complete product range