

## Low Smoke Zero Halogen (LSHF) Covered Flexible Conduit

### PRODUCT FEATURES

- Material: galvanised strip of steel
- Finish: covered with black Low Smoke Zero Halogen Jacket
- Ingress Protection: IP54
- Static temperature range: Static -25°C to +90°C
- Flexing temperature range: -5°C to +90°C
- Flame dies in Less than 30 seconds after the ignition source is removed
- High flexibility with square lock
- High Tensile strength with double interlock
- No hazardous sharp edges or burrs
- Smooth inside for easier wire pulling
- Will not damage conductors
- Provide a grade of water and oil resistant
- Corrosion
- Abrasion
- High fatigue life
- Packed in carton

Type PVC-LSZH



### PRODUCT LIST

| Part Number | Metric Size | External Diameter | Internal Diameter | Min Bend Radius | Coil Packing |
|-------------|-------------|-------------------|-------------------|-----------------|--------------|
| LPOD20LSZH  | 20          | 16.0              | 21.1              | 75              | 30 m         |
| LPOD25LSZH  | 25          | 21.0              | 26.4              | 90              | 30 m         |
| LPOD32LSZH  | 32          | 26.1              | 33.1              | 110             | 20 m         |

### RELATED PRODUCT

| ADAPTORS  | Type A - ZAM  | Type A - MBA  | Type A - FFB   | Type BLT  | Type DLT  |
|---|---|---|--|---|---|
|  |  |  |  |  |  |

all dimensions are nominal value in mm  
refer to our catalogue for the complete product range