

Liquid Resistant PVC Covered Flexible Conduit

PRODUCT FEATURES

- Material: galvanised strip of steel
- Finish: covered with black PVC Jacket
- Ingress Protection: IP54
- Static temperature range: Static -25°C to +50°C
- Flexing temperature range: -5°C to +50°C
- Flame dies in Less than 30 seconds after the ignition source is removed
- High flexibility with square lock
- High Tensile strength with double interlock
- No hazardous sharp edges or burrs
- Smooth inside for easier wire pulling
- Will not damage conductors
- Provide a grade of water and oil resistant
- High fatigue life
- Delivered unpacked

Type PVC-ODL



PRODUCT LIST

Part Number	Metric Size	External Diameter	Internal Diameter	Min Bend Radius	Coil Packing
LPPVC20ODL	20	21.2	17.0	40.0	30 m
LPPVC25ODL	25	25.7	21.1	50.0	30 m
LPPVC32ODL	32	33.0	28.4	60.0	20 m
LPPVC40ODL	40	41.1	36.4	80.0	20 m
LPPVC50ODL	50	54.9	48.2	180.0	10 m

RELATED PRODUCT

ADAPTORS	Type A - ZAM	Type A - MBA	Type A - FFB	Type BLT	Type DLT
					

all dimensions are nominal value in mm
refer to our catalogue for the complete product range